


Medium Profile Hatch

Ideal as a foredeck hatch on larger offshore yachts, the Medium Profile has thicker acrylic and deeper frame sections for greater strength and durability. It features Lewmar's unique sealing system, allowing for easy acrylic replacement. All while retaining the smooth, modern lines of the Low Profile Hatch.



CE Approved Complies with the relevant parts of International Standards ISO/DIS 12216.2002. This standard covers the applicable essential safety requirements of the Recreational Craft Directive 95/25/EC.

Size	Area 2a
All Sizes	✓

Note: Area 2a = Deck, Coachroof, Cockpit & Transom




Medium Profile Hatch — Specifications


Overall Size												Cut-Out Size Dimensions change if Trim kits are used						Hatch Weight		Acrylic Window Thickness	
												Lower Frame Flange		Length		Width					
Part No.	Size	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	kg	lb	mm	in
		X		Y		Z		R		L1		W1		R1							
39930020	30	15	9/16	397	15 5/8	527	20 3/4	32	1 1/4	78	3 1/16	327	12 7/8	457	18	42.5	1 11/16	5.0	11.1	12	1/2
39940020	40	15	9/16	492	19 3/8	492	19 3/8	32	1 1/4	78	3 1/16	421	16 5/16	421	16 5/16	42.5	1 11/16	5.9	13.0	12	1/2
39944020	44	15	9/16	513	20 3/16	513	20 3/16	32	1 1/4	78	3 1/16	442	17 3/8	442	17 3/8	42.5	1 11/16	6.4	14.1	12	1/2
39950020	50	15	9/16	448	17 5/8	578	22 3/4	32	1 1/4	78	3 1/16	377	14 13/16	507	19 15/16	42.5	1 11/16	6.3	13.9	12	1/2
39954020	54	15	9/16	463	18 1/4	578	22 3/4	32	1 1/4	78	3 1/16	392	15 7/16	507	19 15/16	42.5	1 11/16	6.5	14.3	12	1/2
39960020	60	15	9/16	578	22 3/4	578	22 3/4	32	1 1/4	78	3 1/16	507	19 15/16	507	19 15/16	42.5	1 11/16	7.8	17.2	12	1/2
39970020	70	15	9/16	698	27 1/2	698	27 1/2	32	1 1/4	78	3 1/16	627	24 11/16	627	24 11/16	42.5	1 11/16	10.6	23.4	12	1/2
39977020	77	15	9/16	770	30 3/16	770	30 5/8	32	1 1/4	78	3 1/16	699	27 1/2	699	27 1/2	42.5	1 11/16	12.7	28.0	12	1/2

- Hatches should be fitted to a flat surface with a maximum tolerance of $\pm 1\text{mm}$. • Fastening size at the hinge section: use M6 (1/4in) bolts.
- Fastening size for lower frame section: use 5mm CSK screw No. 10 UNC 2BA.
- Cut-out dimensions change if Trim kits are used.
- Size 77 is made to order.


Medium Profile Hatch – Sizes




Size 30




Size 40




Size 44*




Size 50




Size 54*



Size 60




Size 70



Size 77

**Minimum size for EC Escape Hatches
(square and rectangular)*

Medium Profile Hatch — Dimensions



Medium Profile Hatch — Cut-Outs

